



	Size	Standard Rim	PR	Load				Pressure				Load Index TreadDe		Tarrado	0	_ Inflated Tire	
				KG		lbs		kPa		psi		Load Index		TreadDepth (mm)	Speed	Dimention (mm)	
				S	D	S	D	S	D	S	D	S	D	()		D	В
CN	11R22.5	8.25	16	3000	2725	6610	6005	830	830	120	120	146	143	18	К	1054	279
CN	275/70R22.5	8.25	16	3150	2900	6940	6395	900	900	130	130	148	145	17	К	958	275
CN	315/80R22.5	9.00	20	4625	4125	10200	9090	900	900	130	130	161	157	17	G	1076	312
CN	255/70R22.5	7.50	16	2500	2300	5510	5070	830	830	120	120	140	137	17.5	L	930	255
CN	11R24.5	8.25	16	3250	3000	7160	6610	830	830	120	120	149	146	18	Κ	1104	279

The RoadX AP868 All Position tire is engineered for use in both on and off road applications. The AP868 is designed with a wide footprint and solid shoulder ribs to deliver exceptional stability and resistance to uneven wear through equal load distribution. It is constructed with deep tread depth to provide excellent tread life as well as enhanced traction necessary for many applications.

TIRE FEATURES :

- 1 Designed for highway and mixed road surfaces.
- 2 Deep tread depth for excellent tread life.
- 3 Solid shoulder delivers stability in all positions.



