

Wear

Traction

Heat Resistance

-AP869

Resistance

100%

80%

60%

40%

20% 0%

Wet Skid Resistance and

Handling

Tear and Cut

Resistance



	Size	Standard Rim	PR	Load				Pressure				Load	Load Index TreadDepth		Inflated Tire Speed Dimention (mm)		
				KG		lbs		kPa		psi		Load IIIdex		TreadDepth (mm)	Speed Grade	Dimention (mm)	
				S	D	S	D	S	D	S	D	S	D	()	J.aas	D	В
CN	295/80R22.5	9.00	16	3550	3150	7830	6940	850	850	123	123	152	148	17	М	1044	298
CN	315/80R22.5	9.00	18	4000	3350	8820	7385	850	850	123	123	156	150	17	L	1076	312
CN	12.00R24	8.5	20	4500	4125	9920	9090	900	900	130	130	160	157	16	K	1226	315

The AP869 is a mixed service tread tire featuring a chip-resistant compound ideally suited for off-road and construction applications. A zigzag main groove pattern reduces stone retention, while maximizing traction under all applications. Sidewall protectors are engineered to provide an enhanced casing protection.

## TIRE FEATURES:

1 Large deep shoulder groove improves traction and helps the tire run cool.

2 Interlocking lugs promote improve stability and uniform wear.

