

**RH300** REGIONAL  
ALL-POSITION

	Size	Standard Rim	PR	Load				Pressure				Load Index		TreadDepth (mm)	Speed Grade	Inflated Tire Dimension (mm)	
				KG		lbs		kPa		psi		S	D			D	B
				S	D	S	D	S	D	S	D						
VN	6.50R16LT	5.50F	12	1060	925	2335	2040	670	670	97	97	110	105	10.5	L	750	185
CNVN	7.00R16LT	5.50F	14	1320	1180	2910	2600	770	770	112	112	118	114	11.5	L	775	200
CNVN	7.50R16LT	6.00G	14	1500	1320	3305	2910	770	770	112	112	122	118	12.5	L	805	215
CNVN	8.25R16LT	6.50H	16	1800	1600	3970	3525	770	770	112	112	128	124	14	L	865	235

Trailer and steer position tire suitable for trucks traveling medium to long distances on good roads.

Special tread compounding offers excellent wear resistance.

Open shoulder design and heat resistant compounding provide excellent durability.

Four main groove design offers excellent wet skid resistance and handling.

**TIRE FEATURES:**

- 1** Main groove pattern design improve wet skid resistance and handling.
- 2** Open shoulder design and heat resistant compounding provide excellent durability.
- 3** Special composite tread compounding improves wear resistance.

