

CD880R3 LONG HAUL DRIVE

Size	Standard Rim	PR	Load				Pressure				Load Index		TreadDepth (mm)	Speed Grade	Inflated Tire Dimension (mm)	
			KG		lbs		kPa		psi		S	D			D	B
			S	D	S	D	S	D	S	D						
CN 11R22.5	8.25	14	2800	2650	6175	5840	720	720	105	105	144	142	22.5	K	1065	279
CN 11R22.5	8.25	16	3000	2725	6610	6005	830	830	120	120	146	143	22.5	K	1065	279
CN 295/75R22.5	9.00	14	2800	2575	6175	5675	760	760	110	110	144	141	22.5	K	1020	298
CN 11R24.5	8.25	14	3000	2725	6610	6005	720	720	105	105	146	143	22.5	K	1116	279
CN 11R24.5	8.25	16	3250	3000	7160	6610	830	830	120	120	149	146	22.5	K	1116	279
CN 285/75R24.5	8.25	14	2800	2575	6175	5675	760	760	110	110	144	141	22.5	K	1056	283

The RoadX CD880 R3 closed shoulder drive tire features 29/32" tread depth for long tread life and exceptional cost per kilometer. Solid shoulder ribs deliver superior stability and resistance to uneven wear. The CD880 R3 is designed with three rows of aggressive tread blocks for superior traction and resistance to tread squirm. SmartWay verified tires can improve fuel efficiency by 3 percent or more.

TIRE FEATURES:

- 1 Deep tread depth for excellent tread life.
- 2 Aggressive tread design for superior traction.
- 3 Solid shoulders resist uneven wear.

