

DT999 OFF ROAD DRIVE

Size	Standard Rim	PR	Load				Pressure				Load Index		TreadDepth (mm)	Speed Grade	Inflated Tire Dimension (mm)		
			KG		lbs		kPa		psi		S	D			D	B	
			S	D	S	D	S	D	S	D							
CN	11R22.5	8.25	16	3000	2725	6610	6005	830	830	120	120	146	143	24	G	1065	279
CN	12R22.5	9.00	18	3550	3250	7830	7160	930	930	135	135	152	149	23.5	G	1085	300
CN/VN	295/80R22.5	9.00	18	3550	3250	7830	7160	900	900	130	130	152	149	23.5	J	1044	298

Drive tire suitable for short distances on non-paved roads.
Tread compounding improves puncture and tear resistance.
Sturdy pattern that improves traction.
Open block shoulder and wide groove design effectively clean out any foreign objects from the tire.

TIRE FEATURES:

- 1 Tread blocks are designed with central grooves that improve off-road traction.
- 2 The connecting ribs increase shoulder block rigidity to reduce shoulder deformation and prevent block drop-off.
- 3 The ultra-deep pattern design provides strong traction performance and improved mileage.
- 4 Central grooves on the tread blocks allows for efficient heat dissipation during use, providing the tire with great heat resistance.

