

## RH520 REGIONAL STEER

Size	Standard Rim	PR	Load				Pressure				Load Index		TreadDepth (mm)	Speed Grade	Inflated Tire Dimension (mm)	
			KG		lbs		kPa		psi		S	D			D	B
			S	D	S	D	S	D	S	D						
CN 215/75R17.5	6.00	16	2180	2060	4805	4540	860	860	125	125	135	133	12.5	L	767	211
CN 235/75R17.5	6.75	16	2725	2575	6005	5675	860	860	125	125	143	141	13	L	797	233
CN 225/70R19.5	6.75	14	1800	1700	3970	3750	760	760	110	110	128	126	12.5	L	811	226
CN 245/70R19.5	7.50	14	2060	1950	4540	4300	760	760	110	110	133	131	13	K	839	248
CN 255/70R22.5	7.50	16	2500	2300	5510	5070	830	830	120	120	140	137	13.5	L	930	255

The RH520 is a versatile all-position tire for regional use featuring five extra-wide ribs for exceptional stability. An extra-wide solid shoulder resist damage during high-scrub applications, while a mirrored tread design ensures even tread wear. Wide grooves effectively improve wet performance while the special tread compound improves tread life.

### TIRE FEATURES

- 1 Tread sipes improve traction in wet conditions and allow the tire to run cool to extend tread life.
- 2 Shallow tread design reduces rolling resistance for better fuel economy.
- 3 Unique tread wall grooves and sipes help reduce irregular wear.

