

## RH648 LONG HAUL STEER

Size	Standard Rim	PR	Load				Pressure				Load Index		TreadDepth (mm)	Speed Grade	Inflated Tire Dimension (mm)	
			KG		lbs		kPa		psi		S	D			D	B
			S	D	S	D	S	D	S	D						
CN 275/80R22.5	8.25	16	3000	2725	6610	6005	830	830	120	120	146	143	14.5	M	1012	276
CN 295/80R22.5	9.00	16	3550	3150	7830	6940	850	850	123	123	152	148	14.5	M	1044	298
CN 315/80R22.5	9.00	18	3750	3450	8270	7610	830	830	120	120	154	151	15	L	1076	312
CN 315/80R22.5	9.00	20	4125	3750	9090	8270	900	900	130	130	157	154	15	K	1076	312
CN 11R24.5	8.25	14	3000	2725	6610	6005	720	720	105	105	146	143	14.5	M	1104	279
CN 285/75R24.5	8.25	14	2800	2575	6175	5675	760	760	110	110	144	141	14.5	M	1050	283

The RoadX RH648 Regional All Position is optimized for steer axles. The RH648 features a broad 5 rib tread pattern to provide precise handling and excellent stability. Wide circumferential grooves efficiently evacuate water from the tread area and feature "stone ejectors" to prevent stone drilling for a long casing life and improved retreadability. The RH648 is ideally suited for regional line haul applications, pick-up and delivery and highway service. SmartWay verified tires can improve fuel efficiency by 3 percent or more.

**TIRE FEATURES:**

- 1 Broad 5 rib design delivers precise handling.
- 2 Wide circumferential grooves.
- 3 Stone Ejectors minimize stone drilling.

