




The specially formulated compounds are **ECO FRIENDLY**, highly fuel efficient and long lasting.



HP H11 (Red line)      EXISTING PRODUCT (Blue line)



■ **Shoulder Designed**

The closed shoulder design strengthens shoulder blocks for superior handling performance.



■ **Wet Performance**

The three wide tread grooves and wave-like sipes efficiently drain water to improve grip on wet roads and improve driving safety.

■ **Handling**

A pair of center ribs and the solid shoulder blocks maintain stable contact with the road to ensure great handling.

RIM	SIZE	LI/SS		T.D.	STANDARD RIM	S.W.	O.D.	MAX.LOAD	MAX.PRESSURE	UTQG	SIDEWALL
				mm	inch	mm	mm	KG	kPa		
13	145/70R13	71T	--	7	4.50B	150	534	345	300	360/A/A	BSW
13	145/80R13	75T	--	7	4.00B	145	562	387	300	360/A/A	BSW
13	155/65R13	73T	--	7.3	4.50B	157	532	365	300	360/A/A	BSW
13	155/70R13	75T	--	7	4.50B	157	548	387	300	360/A/A	BSW
13	155/80R13	79T	--	7	4.50B	157	578	437	300	360/A/A	BSW
13	165/65R13	77T	--	7.2	5.00B	170	544	412	300	360/A/A	BSW
13	165/70R13	79T	--	7.2	5.00B	170	562	437	300	360/A/A	BSW
13	165/70R13	83T	XL	7.2	5.00B	170	562	487	340	360/A/A	BSW
13	165/80R13	83T	--	7.2	4.50B	165	594	487	300	360/A/A	BSW
13	175/70R13	82T	--	7.2	5.00B	177	576	475	300	360/A/A	BSW
13	185/70R13	86T	--	7.4	5.50B	189	590	530	300	360/A/A	BSW
14	155/65R14	75T	--	7	4 1/2J	157	558	387	300	360/A/A	BSW
14	165/60R14	75H	--	7.2	5J	170	554	387	300	360/A/A	BSW
14	165/65R14	79T	--	7.2	5J	170	570	437	300	360/A/A	BSW
14	165/70R14	81T	--	7.2	5J	170	588	462	300	360/A/A	BSW
14	165/70R14	85T	XL	7.2	5J	170	588	515	340	360/A/A	BSW
14	165/80R14	85T	--	7.2	4 1/2J	165	620	515	300	360/A/A	BSW
14	175/65R14	82T	--	7.2	5J	177	584	475	300	360/A/A	BSW
14	175/65R14	86T	XL	7.2	5J	177	584	530	340	360/A/A	BSW
14	175/70R14	84T	--	7.2	5J	177	602	500	300	360/A/A	BSW
14	175/70R14	88T	XL	7.2	5J	177	602	560	340	360/A/A	BSW
14	185/60R14	82H	--	7.4	5 1/2J	189	578	475	300	360/A/A	BSW
14	185/65R14	86H	--	7.4	5 1/2J	189	596	530	300	360/A/A	BSW
14	185/70R14	88H	--	7.4	5 1/2J	189	616	560	300	360/A/A	BSW
14	185/70R14	88T	--	7.4	5 1/2J	189	616	560	300	360/A/A	BSW
14	195/60R14	86H	--	8	6J	201	590	530	300	360/A/A	BSW
14	195/65R14	89H	--	7.4	6J	201	610	580	300	360/A/A	BSW
14	195/70R14	91T	--	7.4	6J	201	630	615	300	360/A/A	BSW

1inch=25.4mm | 1kPa=0.142psi | 1KG=2.2 lbs | XL Extra Load | LI Load Index | SS Speed Symbol