

# H12

SUMMER-HP



■ **High Performance Safety**

Unique asymmetric pattern design features three main ribs and specially designed blocks which maximize the tire's contact footprint area for great cornering and stability on dry roads.

■ **Driving Safety**

Thin strips on the inside of the groove improve water drainage and better disperse heat.

■ **Wet Performance**

Four main grooves provide efficiently water drainage to improve handling and grip on wet roads.

RIM	SIZE	LI/SS		T.D.	STANDARD RIM	S.W.	O.D.	MAX.LOAD	MAX.PRESSURE	UTQG	SIDEWALL
				mm	inch	mm	mm	KG	kPa		
15	185/55R15	82V	--	7.4	6J	194	585	475	300	360/A/A	BSW
15	185/60R15	84H	--	7.4	5 1/2J	189	603	500	300	360/A/A	BSW
15	185/60R15	88H	XL	7.4	5 1/2J	189	603	560	340	360/A/A	BSW
15	185/65R15	88H	--	7.4	5 1/2J	189	621	560	300	360/A/A	BSW
15	185/65R15	92H	XL	7.4	5 1/2J	189	621	630	340	360/A/A	BSW
15	195/45R15	78W	--	7.4	6 1/2J	195	557	425	300	360/A/A	BSW
15	195/50R15	82V	--	7.4	6J	201	577	475	300	360/A/A	BSW
15	195/55R15	85V	--	7.4	6J	201	595	515	300	360/A/A	BSW
15	195/60R15	88H	--	7.4	6J	201	615	560	300	360/A/A	BSW
15	195/60R15	88V	--	7.4	6J	201	615	560	300	360/A/A	BSW
15	195/65R15	91H	--	7.4	6J	201	635	615	300	360/A/A	BSW
15	195/65R15	91V	--	7.4	6J	201	635	615	300	360/A/A	BSW
15	195/65R15	95H	XL	7.4	6J	201	635	690	340	360/A/A	BSW
15	205/50R15	89V	XL	7.7	6 1/2J	214	587	580	340	360/A/A	BSW
15	205/60R15	95V	XL	7.7	6J	209	627	690	340	360/A/A	BSW
15	205/65R15	94V	--	7.7	6J	209	647	670	300	360/A/A	BSW
15	205/70R15	96H	--	7.7	6J	209	669	710	300	360/A/A	BSW
15	215/60R15	98V	XL	7.7	6 1/2J	221	639	750	340	360/A/A	BSW
15	215/65R15	96V	--	7.7	6 1/2J	221	661	710	300	360/A/A	BSW
15	215/70R15	98H	--	7.7	6 1/2J	221	683	750	300	360/A/A	BSW
15	225/60R15	96V	--	7.7	6 1/2J	228	651	710	300	360/A/A	BSW
16	185/55R16	83V	--	7.4	6J	194	610	487	300	360/A/A	BSW
16	195/45R16	84W	XL	7.4	6 1/2J	195	582	500	340	360/A/A	BSW
16	195/50R16	88V	XL	7.4	6J	201	602	560	340	360/A/A	BSW
16	195/55R16	87V	--	7.4	6J	201	620	545	300	360/A/A	BSW
16	195/55R16	91V	XL	7.4	6J	201	620	615	340	360/A/A	BSW
16	195/60R16	89V	--	7.4	6J	201	640	580	300	360/A/A	BSW
16	205/45R16	87W	XL	8	7J	206	590	545	340	360/A/A	BSW
16	205/55R16	91V	--	7.7	6 1/2J	214	632	615	300	360/A/A	BSW
16	205/55R16	94V	XL	7.7	6 1/2J	214	632	670	340	360/A/A	BSW
16	205/60R16	92V	--	7.7	6J	209	652	630	300	360/A/A	BSW
16	205/60R16	96V	XL	7.7	6J	209	652	710	340	360/A/A	BSW
16	205/65R16	95H	--	7.7	6J	209	672	690	300	360/A/A	BSW
16	215/60R16	95V	--	7.7	6 1/2J	221	664	690	300	360/A/A	BSW
16	215/65R16	98H	--	7.7	6 1/2J	221	686	750	300	360/A/A	BSW
16	225/60R16	102V	XL	7.7	6 1/2J	228	676	850	340	360/A/A	BSW
16	235/60R16	100V	--	8	7J	240	688	800	300	360/A/A	BSW

1inch=25.4mm | 1kPa=0.142psi | 1KG=2.2 lbs | XL Extra Load | LI Load Index | SS Speed Symbol

## ROADX

# ENVIRONMENTALLY FRIENDLY

compound formulation with HD Silica and advanced SBR to ensure safety while driving.

